HIGH PERFORMANCE COATINGS

R



HIGH HEAT JUST GOT HOTTER!

It's always been about the heat at VHT. Now we've rolled out new packaging and improved your project results with the new Danvern[®] EZ Touch nozzle. So now you'll get even hotter results ... but we didn't change what you've come to expect from VHT ... "Extreme High Heat Performance". Through the years, the VHT brand has been the motorsport enthusiasts' choice for high-heat applications. It could withstand such extreme high-heat temperatures that it found its way into the space program and was used on space bound and atmospheric re-entry spacecraft. It doesn't get much hotter than that. Our FlameProof[™] line can withstand temperatures of up to 2000°F ... perfect for your exhaust systems, turbo housings, piston domes and exhaust valves.

VHT also offers other High Heat products for applications ranging from 250°F (121°C) - 900° F (482°C): High Temp Engine Enamel[™], Caliper Paint, Wheel Paint, Wrinkle Plus[™] and Roll Bar & Chassis.

VHT's complete line-up includes products for your automotive exterior and interior dress-up applications. Check it out in the pages of this catalog ... Or hit vhtpaint.com to learn more!



WHAT'S INSIDE

VHT FLAMEPROOF [™] COATING
VHT ENGINE METALLIC [™]
VHT ENGINE ENAMEL [™]
VHT WRINKLE PLUS™ COATINGS
VHT CALIPER PAINT
VHT ANODIZED COLOR COAT
VHT WHEEL PAINT
VHT ROLL BAR & CHASSIS PAINT
VHT STRIP FAST [™]
VHT RUST CONVERTOR
VHT EPOXY ALL WEATHER PAINT
VHT HOOD, BUMPER & TRIM PAINT
VHT PLATE FINISH [™]
VHT NITE-SHADES™15
VHT VINYL DYE [™]
VHT COPPER GASKET CEMENT
VHT PRIME COAT™ 17
VHT QUICK COAT TM
VHT BLACK OXIDE CASE PAINT
VHT BARREL SPRAY PAINT

Flat Gray Primer SP100 0-10155-00100-5

Flat White SP101 0-10155-00101-2

Flat Black SP102 0-10155-00102-9

Flat Gray SP104 0-10155-00104-3



SP106 0-10155-00106-7





Flat Red SP109 0-10155-00109-8



Flat Orange SP114 0-10155-00114-2



Satin Clear SP115 0-10155-00115-9



Flat Aluminum SP117 0-10155-00117-3



Flat White Primer SP118 0-10155-00118-0



Nu-Cast™ Cast Iron SP998 0-10155-00998-8

HEADER PAINT SILICA - CERAMIC COATING

VERY HIGH TEMPERATURE

^{1300-2000°F} (704-1093°^{C)}

MIGER! DETREMELY FLANIMABLE - VAPORS MAY CAUSE FLAST DETRIBUTE INFORMATION FLANIMABLE - VAPORS MAY CAUSE FLAST TERTS UNDER PRESSURE, VAPOR HARNFUL, BRITATES PRESSURE, VAPOR HARNFUL, BRITATES PRESSURE, VAPOR HARNFUL, BRITATES PRES TOPPENDER PRESSURE, VAPOR HARNER, WENTALLS ELCO.

NET WT. 11 OZ (3129)

VHT FLAMEPROOF™ COATING

VHT FlameProof[™] Coating will renew and extend the life of any surface exposed to extremely high temperatures. This unique coating is a matte finish, silicone ceramic base widely used by the automotive industry on exhaust systems and the aerospace industry for jet engines, re-entry vehicles and other high temperature applications. VHT FlameProof[™] Coating will withstand temperatures up to 2000°F (1093°C) and is ideal for use on headers, exhaust systems, or wherever an extreme temperature coating is needed.

11 oz can — Case pack: 6

Temperature: 1300°F-2000°F (704°C-1093°C)

Applications: Headers, Exhaust Manifolds, Piston Domes, Inside Heads

Finish: Flat

Dry Time: Curing time required and can be done on or off vehicle (see below)

Curing FlameProof™

VHT FlameProof[™] Coating only attains its unique properties after correct curing (refer to instructions on the can).

On the Vehicle

- Paint must be completely dry before curing
- Run at idle for 10 minutes
- Cool for 20 minutes
- Run at idle for 20 minutes Cool for 20 minutes
- Run under normal operating conditions for 30 minutes

Off the Vehicle

- Paint must be completely dry before curing
- Heat to 250°F (121°C) for 30 minutes
- Cool for 30 minutes
- Heat to 400°F (204°C) for 30 minutes
- Cool for 30 minutes
- Heat to 650°F (343°C) for 30 minutes

CAUTION: Do not exceed the temperature of the least heat tolerant component or the base metal

Coating System VHT provides a multi-high

performance coating system for the ultimate in protection and quality. The system includes surface preparation, primer, paint and clear coat.

Prep	SP575	Strip Fast
Prime	SP118	FlameProof [™] Primer
Coat	SPXXX	FlameProof [™] Color
Finish	SP115	FlameProof™ Clear

VHT ENGINE METALLIC™

Under hood engine dress-up never looked this good, or stood up to high-heat temperatures like VHT Engine Metallic[™] Paint. Formulated for high temperature and high performance applications, VHT Engine Metallic Paint[™] creates a cool sparkling metallic finish and withstands intermittent temperatures of up to 650°F (343°C). A unique formulation of urethane and ceramic resins produces a tough and long lasting finish for engines, engine accessories, or any other surface that requires a durable, heat and chemical resistant finish.

11 oz can — Case pack: 6

Temperature: 650°F (343°C)

Applications: Headers, Engine Blocks, Starters, Brackets, Water Pumps, Valve Cover, Transmissions, Differential Covers

Finish: Flat Metallic

Dry Time: Dries to the touch in 30 mins. Dries thoroughly overnight.

Curing Engine Metallic™

VHT Engine Metallic[™] only attains its unique properties after correct curing.

• Bake at 200°F (93°C) for 20 min

• The inherent heat of engine operation will also accomplish curing.

Coating System VHT provides a multi-high performance coating system for the ultimate in protection and quality. The system includes surface preparation, primer, paint and clear coat.

Prep	SP575	Strip Fast
Prime	SP148	Engine Primer (Optional - 550°F)
Coat	SPXXX	Engine Metallic™
Clear	SPXXX	Engine Clear (Optional - 550°F)


Red Fire SP401 0-10155-46207-3

Burnt Copper SP402 <u>0-10</u>155-46208-0

Titanium Silver Blue SP403 0-10155-46209-7

> Gold Flake SP404 0-10155-46210-3

Black Pearl SP405 0-10155-00007-7





Motor Brite - Clear Engine Enamel SP29 0-10155-00029-9

Chevy Orange Red SP119 0-10155-00119-7

Chrysler Hemi-Orange SP120 0-10155-00120-3

Universal Bright Red SP121 0-10155-00121-0

Pontiac Blue SP122 0-10155-00122-7

Chevy Orange SP123 0-10155-001<u>23-</u>4

Gloss Black

SP124 0-10155-00124-1

Ford Dark Blue SP125 0-10155-00125-8



Early c Blue SP126 0-10155-00126-5

Universal Aluminum SP127 0-10155-00127-2

Gloss Yellow SP128 0-10155-00128-9



SP129 0-10155-00129-6 Flat Black SP130 0-10155-00130-2

Gloss White



Ford Green SP131 0-10155-00131-9



Ford Light Blue SP134 0-10155-00134-0



GM Blue SP135 0-10155-00135-7 Ford Gray SP137 0-10155-00137-1

New Ford Blue SP138 0-10155-00138-8

GM Satin Black SP139 0-10155-00139-5

Gloss Clear SP145 0-10155-00145-6

Light Gray Primer SP148 0-10155-00148-7

Racing Green SP151 0-10155-04443-9

Ford Red SP152 0-10155-04442-2

Old Ford Blue SP153

0-10155-00016-9

Grabber Green SP154 <u>0-10155-000</u>15-2

Chrysler Red SP155 0-10155-00017-6

Competition Ford Blue

0-10155-00755-7 Kermit Green

SP760 0-10155-00760-1

Concourse Ford Blue SP761 0-10155-00761-8

Nu-Cast™Aluminum SP995 0-10155-00995-7

Nu-Cast™ Cast Iron SP997 0-10155-00997-1

GM Holden Blue SP1202 0-10155-01202-5

VHT ENGINE ENAMEL™

VHT 550°F (288°C) Engine Enamels[™] are available in a wide range of colors, including exact match factory colors. All colors have excellent durability and superior heat and chemical resistance. They are specially formulated to withstand corrosion, rust, salt spray, chemicals and additives of today's gasoline blends and degreasers. VHT 550°F (288°C) Engine Enamels[™] are a unique blend of urethane and ceramic resins, which produce a tough and long-lasting finish for engines, engine accessories or wherever a tough durable heat or chemical resistant finish is needed.

11 oz can — Case pack: 6

Temperature: 550°F (288°C)

Applications: Headers, Engine Blocks, Starters, Brackets, Water Pumps, Valve Cover, Transmissions, Differential Covers

Finish: Flat, Satin, Gloss and Metallic

Dry Time: Dries to the touch in 30 mins. Dries thoroughly overnight.

Curing Engine Enamel

VHT Engine Enamel only attains its unique properties after correct curing.

- Bake at 200°F (93°C) for 20 min
- The inherent heat of engine operation will also accomplish curing.

Coating System VHT provides a multi-high performance coating system for the ultimate in protection and quality. The system includes surface preparation, primer, paint and clear coat.







VHT WRINKLE PLUS™ COATINGS

VHT Wrinkle Plus[™] combines strong colors with a deep rich texture for a custom look. It is temperature resistant to 350°F (177°C) and is ideal for adding a touch of personal styling to almost any metal surface. VHT Wrinkle Plus[™] resists color fading, grease, degreasers and severe weather conditions. This tough durable finish is extremely resistant to rust, corrosion, chipping and cracking.

11 oz can — Case pack: 6

Temperature: 350°F (177°C)

Applications: Valve Covers, Metal Dashboards, Glove Boxes, Starters, Door Panels, Shifters, Alternators, Firewalls

Finish: Flat

Dry Time: Dries within 24 hrs.

Curing Wrinkle Plus™

VHT Wrinkle Plus[™] only attains its unique properties after correct curing.

• Bake at 200°F (93°C) for 20 min.

• The inherent heat of engine operation will also accomplish curing.

Coating System VHT provides a multi-high

performance coating system for the ultimate in protection and quality. The system includes primer and paint.

Prime	SP148	Engine Prime
Coat	SPXXX	Wrinkle Plus [™] Color

Black SP201 0-10155-00201-9





WRINKLE FINISH DURABLE TEXTURE COATING

350°F (177°C)

GER! EXTREMELY FLAMINABLE - VAPORS MAY CAUSE FURNING WARE PERSONNEL

Caliper CLeaner SP700 0-10155-52490-0 Gloss Clear SP730 0-10155-00730-4 Real Red SP731 0-10155-00731-1 Bright Blue SP732 0-10155-00732-8 Real Orange SP733 0-10155-00733-5 Gloss Black SP734 0-10155-00734-2 Cast Aluminum SP735 0-10155-00735-9 Gold SP736 0-10155-00736-6 Bright Yellow SP738 0-10155-00738-0 Satin Black SP739 0-10155-00739-7

VHT CALIPER PAINT

VHT Brake, Caliper, Drum & Rotor Coatings have been specifically designed for the custom detailing of brake components. It is heat resistant to 900°F (482°C) and will not chip, crack, fade or rust even under extremes of operation or road and weather conditions. It is easy to apply, dries quickly and is remarkably resistant. Careful preparation is essential.

11 oz can — Case pack: 6

Temperature: 900°F (482°C)

Applications: Brake Calipers, Rotors, Brake Drums

Finish: Satin and Gloss

Dry Time: Dries to touch in 30 mins. Dries thoroughly overnight.

Curing Caliper Paint


VHT Caliper Paint only attains its unique properties after correct curing.

- Bake at 200°F (93°C) for 20 min.
- The inherent heat of braking operation will also accomplish curing.

Coating System VHT provides a multi-high

performance coating system for the ultimate in protection and quality. The system includes prep, primer, paint and clear coat.

Prep	SP700	Caliper Cleaner
Prime	SP118	Flame Proof Primer
Coat	SPXXX	Brake Color
Finish	SP730	Gloss Clear



900°F (482°C)

ANGER! EXTREMELY FLAMMABLE - VAPORS MAY CAUSE FLAM



VHT ANODIZED COLOR COAT

Now DIYers can create an anodized look under their hoods. This unique transparent coating creates an anodized effect over properly prepared chrome, shiny bare metal and faux chrome-like surfaces for a spectacular metallic finish. VHT Anodized Color Coat is formulated for high temperature and high performance engine paint applications. It withstands intermittent temperatures up to 550°F (228°C).

VHT ANODIZED BASE COAT

To create the anodized metal look over non-metal and/or painted surfaces, first prime with VHT Anodized Base Coat. Then apply VHT Anodized Color Coat when dry.

11 oz can — Case pack: 6

Temperature: 550°F (228°C)

Applications: Engine Components, Chrome Wheels, Bumpers, Trim, Accessories

Finish: Translucent Gloss Color

Dry Time: Dries to the touch in 30 mins. Dries thoroughly overnight. No curing required.

Coating System VHT provides a multi-high performance coating system for the ultimate in protection and quality. The system includes a recommended adhesion promoter, paint and clearcoat.

Coat	SPXXX	Anodized Color	
Clear	SP145	Engine Gloss Clear	



Anodized Blue SP451 0-10155-46212-7

Anodized Purple SP452 0-10155-46213-4

Anodized Base Silver SP453 0-10155-46214-1





550°F (228°C)

ITER CONTAINES & PESSEE REV PECANONS PROPERTIES AND EMP VTENTE UNDER PRESER REV EMP 7 REVE CASTONY IN METAME.

DVER RFACE

0G)

HE

REPART AND A

Aluminum SP181 0-10155-00181-4

Satin Black SP183 0-10155-00183-8

Clear Coat SP184 0-10155-00184-5

Chevy Rally Silver SP186 0-10155-00186-9

Gloss Black SP187 0-10155-00187-6

Ford Argent Silver SP188 0-10155-00188-3

Graphite SP189 0-10155-00018-3

<section-header>

GERI

VHT WHEEL PAINT

VHT Wheel Paint provides a great finish and real protection for all standard and custom wheels. Every day wheels take a beating both on and off the road. Salt, sand, brake dust and rocks severely damage the appearance and protection of the wheel surface. This unique product resists chipping, cracking and fading, while protecting the wheel surface from oxidation, and is available in five popular colors plus clear coat.

11 oz can — Case pack: 6

Temperature: 250°F (121°C)

Applications: Aluminum Wheels, Steel Wheels, Wheel Covers, Center Caps

Finish: Satin and Gloss

Dry Time: Dries to the touch in 30 mins. Dries thoroughly overnight. No curing required.

Coating System VHT provides a multi-high performance coating system for the ultimate in protection and quality. The system includes primer, paint and clear coat.

Prime	SP148	Engine Primer	
Coat	SPXXX	Wheel Paint Color	
Clear	SP184	Clear Coat	



VHT ROLL BAR & CHASSIS PAINT

VHT Roll Bar & Chassis Paint is a one step epoxy coating that does not require primer. It gives the appearance of a tough baked-on finish that is chemical, corrosion, rust and salt resistant.

11 oz can — Case pack: 6

Temperature: 250°F (121°C)

Applications: Frame & Chassis, Shop Racks, Tools & Equipment, Trailers

Finish: Gloss and Satin

Dry Time: Dries to the touch in 30 mins. Dries thoroughly overnight. No curing required.

Coating System VHT provides a high performance coating for the ultimate in protection and quality.

Beat	000/0/0/	Dell Dev Oelev	
Coat	SPXXX	Roll Bar Color	



Gloss Black SP670 0-10155-00670-3

Satin Black SP671 0-10155-00671-0

V	T SI	R	P	15	тм

VHT Strip Fast[™] Paint Remover is the absolute best paint remover on the market today. This extremely effective formula bubbles and removes lacquers, enamels, acrylics, varnishes and oils from metal and wood. Used by many championship race teams and restorers.

11 oz can — Case pack: 6

Temperature: n/a

Applications: Suspension and chassis parts, Race car body panels (metal only), Painted engine components, Shop items, Household items, Any wood or metal surface

Finish: n/a

Dry Time: n/a

Coating System VHT provides a high performance coating for the ultimate in protection and quality.

Coat	SP575	Strip Fast







COLUMN FLORIDA - WHILE AN OWNER



RUST CONVERTOR SP229 0-10155-36876-4

Gloss Black SP650 0-10155-00650-5

Gloss White SP651 0-10155-00651-2

Satin Black

0-10155-00652-9

SP652



SPECIALTY PRODUCTS

- SELF PRIMING - ALL WEATHER RUST & SALT RESISTANT 250°F (121°C)

VHT RUST CONVERTOR

VHT Rust Convertor destroys rust on contact. It sprays on clear and turns to a black metal-protecting coating to prevent future rust from forming. Specifically formulated for application over metal, body filler or fiberglass, Rust Convertor sands to a smooth, even finish.

11 oz can — Case pack: 6

Temperature: n/a

Applications: Rusted Metal Surfaces

Finish: Flat

Dry Time: Allow 24 hours before applying top coat.

Coating System VHT provides a high performance coating for the ultimate in protection and quality.

Coat SP229

Rust Convertor

VHT EPOXY ALL WEATHER PAINT

VHT Epoxy Paint is a one-step epoxy coating, which does not require the use of a primer. It has been formulated to give the appearance and durability of a baked-on finish. It provides a porcelain-like finish that is chemical, corrosion, rust and salt resistant.

11 oz can — Case pack: 6

Temperature: 250°F (121°C)

Applications: Suspension, Kick Panels, Tools

Finish: Gloss and Satin

Dry Time: Dries to the touch in 30 mins. Dries thoroughly overnight. No curing required.

Coating System VHT provides a high performance coating for the ultimate in protection and quality.

Coat SPXXX Epoxy Color

VHT HOOD, BUMPER & TRIM PAINT

VHT Hood, Bumper & Trim urethane coating is formulated with elastomers that allow for the flexing of paint on pliable surfaces. This unique formula is also well suited for fiberglass, plastic and other resin based bodywork. Equally suited for metal. VHT Hood, Bumper & Trim Paint offers excellent hide and mar resistance.

11 oz can — Case pack: 6

Temperature: n/a

Applications: Plastic Bumpers, Rubber Bumpers, Body Trim, Kick Panels, Dash Boards, Mirror Castings, ATV Body Work, Motorcycle Body Work

Finish: Satin

Dry Time: Dries to the touch in 30 minutes. Dries thoroughly overnight. No curing required.

Coating System VHT provides a high performance coating for the ultimate in protection and quality.

Coat SP27 Black



Chrome Plus SP5251 0-10155-05251-9

Black SP27

0-10155-00027



VHT PLATE FINISH™

VHT Plate Finish[™] is a unique quick drying formulation specifically created for application on metal, glass, and wood or sealed plaster surfaces. This non-tarnishing epoxy finish has outstanding corrosion resistance. VHT Plate Finish[™] is easy to use and dries in minutes. Excellent for touch-up, refinishing and decorative applications.

11 oz can — Case pack: 6

Temperature: n/a

Applications: Instrumentation, Picture Frames, Tail Light reflectors, Pottery, Lamps, Outdoor Lighting

Finish: High Gloss

Dry Time: Dries to the touch in 30 mins. Dries thoroughly overnight. No curing required.

Coating System VHT provides a high performance coating for the ultimate in protection and quality.

Coat SP5251 Chrome Plus



SERI DIRIKAN HANNAKI - WANA MU CARLAN RU ANA PARAMU WAN NANALI MUTA MU CARLAN RUMAT MACLANIA ANA ANA ANA ANA ANA



Lens Cover Tint SP999 0-10155-00999-5

Nite Shades Red SP888 0-10155-00003-9

VHT NITE-SHADES™

VHT Nite-Shades[™] is a transparent black tail light lens coating for creating a custom European styling. When applied to tail lights, fog lights or turn indicators, VHT Nite-Shades[™] appears black until they are lit, then the natural red color appears. Recommended for off road use. Warning: Once applied to plastic lens, SP999 is not able to be satisfactorily removed.

10 oz can — Case pack: 6

Temperature: n/a

Applications: Tail Lights, Fog Lights, Turn Indicators

Finish: Gloss


Dry Time: Dries to the touch in 1 hour. Dries thoroughly overnight. No curing required.

Coating System VHT provides a high performance coating for the ultimate in protection and quality.

Coat SPXXX Nite-Shades™



NULER! DITREMELY FLANMABLE -Instituter pressure. Work Ha




And a state of the state of the

IN COLUMN TWO IS NOT THE OWNER OF THE OWNER OWN

MIZE AND REST

10





Copper Gasket SP21A 0-10155-04456-9



VHT COPPER GASKET CEMENT

VHT Copper Gasket Cement has been formulated with the same ingredients as our world-renowned high temperature coatings. VHT Copper Gasket Cement maintains excellent adhesion under severe pressure and heat fluctuations. This high metallic formula assures tight seals on cork, paper and metal gaskets. VHT Copper Gasket Cement has been extensively tested on racing engines in the field and on dynamometers, where it has met and exceeded the high compression and high temperature requirements of these mega horsepower engines.

12 oz can — Case pack: 6

Temperature: n/a

Applications: Head Gaskets, Rubber Hoses, Cork Gaskets, Water Pump Gaskets, Threaded Fittings, AN Fittings, Paper Gaskets, Oil Pan Gaskets, Metal Gaskets

Coating System VHT provides a high performance coating for the ultimate in protection and quality.

Coat SP21A Copper Gasket



16

White **SP301**

0-10155-00301-6

Dark Gray SP302 0-10155-00302-3

Red Oxide SP303 0-10155-00303-0

Light Gray SP304 0-10155-00304-7

Black SP305 0-10155-00305-4

Yellow Zinc Chromate (For Aluminum) SP306 0-10155-00306-1

Self-Etching Primer SP307 0-10155-49254-4



VHT

SPECIALTY PRODUCTS AJSIN

VHI



VHT Prime Coat[™] is an excellent foundation for any enamel, acrylic or synthetic lacquer. It provides a tough, air-dry base with excellent adhesion to intermediate and top coatings. VHT Prime Coat is specially formulated to fill scratches or pin holes caused by sanding or body fillers to form a strong corrosion barrier. It is a multi-purpose product, and can be used on metal, fiberglass, masonry, wood and most plastic surfaces. It is ideal for automotive, marine, aviation, home, farm, and industrial use.

11 oz can — Case pack: 6

Temperature: n/a

Applications: Before Paint Coating, Fills in small scratches, Increases bond

Finish: Flat

1111

Dry Time: Primer will dry in 30-45 minutes for sanding purposes.

Coating System VHT provides a multi-high performance coating system for the ultimate in protection and quality. The system includes Strip Fast™ and Prime Coat[™].

Prep	SP575	Strip Fast™	
Prime	SPXXX	Prime Coat [™] Color	



Bright Orange SP503

0-10155-00503-4

Gloss Black SP504 0-10155-00504-1



Ocean Blue SP505 0-10155-00505-8

Bright Aluminum

0-10155-00507-2



Bright Yellow SP508 0-10155-00508-9

SP507



Gloss White SP509 0-10155-00509-6

Flat Black SP510 0-10155-00510-2

Forest Green SP512 0-10155-00512-6

Machinery Gray SP513 0-10155-00513-3



Silver Chrome SP525 0-10155-00525-6

0-10155-00515-7

Clear

SP515



VHT QUICK COAT™

VHT Quick Coat[™] Enamel is a premium quality coating, which provides extra hide and durability for interior or exterior applications. This tough and durable coating prevents rust and corrosion on properly prepared surfaces, is fast drying, lead free and ozone safe. VHT Quick Coat™ Enamel provides a rich weather resistant gloss finish to wood, metal, sealed plaster and masonry surfaces.

11 oz can — Case pack: 6

Temperature: n/a

Applications: Tools, Wood, Household Projects

Finish: Satin, Gloss and Flat Dry Time: Dries to the touch in 30 mins. Dries thoroughly overnight. No curing required.

Coating System VHT provides a multi-high performance coating system for the ultimate in protection and quality. The system includes primer, paint and clear coat.

Prime	SPXXX	Prime Coat [™] Color
Coat	SPXXX	Quick Coat [™] Color
Clear	SP515	Quick Coat [™] Clear

VHT BLACK OXIDE CASE PAINT

VHT Black Oxide Case Paint is a satin finish high temperature coating developed specifically for 2 and 4-stroke motorcycle engines. It is petrol and solvent resistant, and virtually stops rust and corrosion, even in severe weather conditions.

11 oz can — Case pack: 6

Temperature: 550°F (288°C)

Applications: Small Motorsports Engines

Finish: Satin

Dry Time: Dries to the touch in 30 mins. Dries thoroughly overnight.

CURING BLACK OXIDE CASE PAINT

VHT Black Oxide Case Paint only attains its unique properties after correct curing.
The inherent heat of engine operation will accomplish curing.

COATING SYSTEM

Coating System VHT Provides a multi-high performance coating system for the ultimate in protection and quality. The system includes surface preparation, primer, paint and clear coat.

Prep	SP575	Strip Fast	
Prime	SP148	Engine Primer	
Paint	SP903	Case Paint	
Clear	SPXXX	Engine Clear	



VHT BARREL PAINT

VHT Barrel Spray Paint is custom formulated to restore motorcycle engines to their original factory appearance. It is extremely resistant to oil, petrol and solvents, and is heat resistant to 550°F (288°C). It virtually stops rust and corrosion while resisting chipping, cracking and fading.

11 oz can — Case pack: 6

Temperature: 550°F (288°C)

Applications: Small Motorsport Engines

Finish: Gloss, Satin

Dry Time: Dries to the touch in 30 mins.

Dries thoroughly overnight.

CURING BARREL PAINT

VHT Barrel Paint only attains its unique properties after correct curing. • The inherent heat of engine operation will accomplish curing.

COATING SYSTEM

Coating System VHT Provides a multi-high performance coating system for the ultimate in protection and quality. The system includes surface preparation, primer, paint and clear coat.

Prep	SP575	Strip Fast	
пер	01070	01119 1 431	V
Prime	SP148	Engine Primer	
Paint	SPXXX	Barrel Paint	
Clear	SPXXX	Engine Clear	

Gloss Black SP905 0-10155-00905-6 Satin Black SP906 0-10155-00906-3

Satin Black



ALL CATALONIST I ANDRONAL - MANDEL AND CARACTERISTICS Design Processory, March Statement, Balance Prosense Dance Statement of the Statement of the Statement of the Statement Dance Statement of the Statement o

HIGH HEAT JUST GOT HOTTER AT VHTPAINT.COM

You'll always find something new at vhtpaint.com...new products, new promotions, and now The Winner's Circle. Share your VHT success stories in The Winner's Circle, or read up on the successes other DIYers have had using VHT products on their motorcycles, cars, trucks, ATV's, and other vehicles. Check it out today!



VH

211

(VHT)

CÌ

VHT



VHT

ENGINE METALLIC*

(VHT)

VHT

Day Theas Co Curing Fla VICT Flama Pro On the Ve Palet inset to
 Run at tota fo
 Cost for 20 m
 Run at tota fo
 Bun at tota fo
 Bun at tota fo
 Bun at tota fo
 Bun and tota fo

HIGH HEATING

VHT

JG

VHT FLAMEPROOF" COATING



See 2

(VHT)

ACC 2.42

Off the V And the second s



AVAILABLE IN THESE COLORS B OF AL Gas Mine

· SPICE For Man

19

